

## LED light bar Order form

Blinds by Peter Meyer orders@petermeyerblinds.com.au www.weinoraustralia.com.au  Customer name			Quote/offer Order Order number/reference	
			Customer requested delivery date	
			Different delivery address to normal/miscellaneous	
Customer number				
wein	or sales representat	ive	_	
			_	
Light bar			Accessories	
	LED light bar		2.5 m cable track with adhesive tape	
	LED Design round li	aht bar	Roof mounting kit (LED light bar)	
			Holder adjustable (LED Design light bar)	
	LED Design square	light par	Primarily cable 3200 AMP/OE 3,2 m (coupling LED Design	
LED Design 3Spot round light bar			Connecting cable 3200 Wieland 3,2 m (coupling LED Design); mandatory required for control with radio receive	
	LED Design 3Spot s	quare light bar		
Quan	tity		BiConnect radio receiver	
\\/id+k	h (length of light bai	r)mı	BiRec LED (radio dimmer LED light)	
			BiConnect radio transmitter	
Connection and control from 2 light bars  Each bar with its own individual connection cable and			BiEasy 1M BiEasy 5M	
control unit Coupling/connecting cable between the bars with single			BiEasy 15M BiEasy 15M Go!	
	nnection and contro		BiEasy 1MW-3V (wall transmitter, white)	
		light bars   Somfy max. 3 light bar		
is possible with a single control. With the connecting cable the light bars can be placed approx. 2 metres apart. For more informtion see technical product catalogue.			Diack Silver	
			Equipment for app operation	
Colour			BiEasy Set includes BiEasy Box und BiEasy Stick	
RA	L colour	Trend colour	Somfy radio receiver (not dimmable)	
Colour name			Lighting Receiver Variation on/off io	
Cable	e exit (seen from out	side)	Variation on/on to	
lef		right	Somfy hand transmitter	
			Situo 1 io Pure II Situo 1 RTS Pure II	
		ding to the valid general terms of	Situo 5 io Pure II Situo 5 RTS Pure II	
delivery and payment of weinor.			Situo 5 Variation A/M Situo 1 Soliris RTS Pure II	
Signature			io Pure II Situo 5 Soliris RTS Pure II	