

Blinds by Peter Meyer
orders@petermeyerblinds.com.au
www.weinoraustralia.com.au

Customer name

Customer number

weinor sales representative

Order number/reference

Order date

Customer requested delivery date

Different delivery address to normal/miscellaneous

Topas, without roof	<input type="checkbox"/>	I 2000	<input type="checkbox"/>
Topas, with roof	<input type="checkbox"/>	K 2000	<input type="checkbox"/>
Semina	<input type="checkbox"/>	N 2000	<input type="checkbox"/>

Quantity _____ No. of arms _____

Width _____ Projection angle _____

For 2-piece systems (not for N 2000, Semina and MiniMax):

Jockey cover Sliding support

Frame colour

RAL colour Trend colour

Colour name _____

Fabric

Fabric sewn with PTFE yarn

Pattern no. _____

Valance (height 20 cm)

Shape no. _____ Quantity _____

Height _____ Edge binding no. _____

With BiConnect radio control

yes no

Motor drive (viewed from the outside)

Standardmotor left Standardmotor right

Somfy RTS motor Somfy io-homecontrol® radio motor

Caution! The BiConnect radio control can only be delivered with the standardmotor.

Quote/offer Order

Gear drive left right

Length of handle (in mm)

800 1000 1200 1400 1600 1800 2000

BiConnect radio control

BiConnect sensors

<input type="checkbox"/> BiSens SW 230V	<input type="checkbox"/> BiSens SWR 230V
<input type="checkbox"/> BiSens SW Solar+	<input type="checkbox"/> BiSens Agido-3V

BiConnect radio transmitter

<input type="checkbox"/> BiEasy 1M	<input type="checkbox"/> BiEasy 5M
<input type="checkbox"/> BiEasy 15M Go!	<input type="checkbox"/> BiEasy 1MW-3V (wall transmitter, white)

The hand transmitter is available in two colours to choose from

black silver

Somfy hand transmitter

<input type="checkbox"/> Situo 1 io Pure II	<input type="checkbox"/> Situo 1 RTS Pure II
<input type="checkbox"/> Situo 5 io Pure II	<input type="checkbox"/> Situo 5 RTS Pure II
<input type="checkbox"/> Situo 5 Variation A/M io Pure II	<input type="checkbox"/> Situo 1 Soliris RTS Pure II <input type="checkbox"/> Situo 5 Soliris RTS Pure II

Somfy controls (separate order form)

Fixing brackets

Installation on C20/25 concrete walls with a casing of up to 200 mm, wind resistance class 2 and a permissible centric tensile load for anchor bolts of 5.71 kN.

For other surfaces/assembly configurations, please enter the quantity and article number of the relevant brackets.

Quantity _____ Article no. _____

Quantity _____ Article no. _____

Or Enter the quantity of the required brackets/mounting plates individually (in pieces):

Standard wall bracket 85 mm	<input type="checkbox"/>	Wall bracket 260 mm	<input type="checkbox"/>
Ceiling bracket with standard wall bracket (85 mm)	<input type="checkbox"/>	Ceiling bracket compact (only Topas without top)	<input type="checkbox"/>
Rafter bracket left + standard wall bracket	<input type="checkbox"/>	Rafter bracket right + standard wall bracket	<input type="checkbox"/>
Rafter bracket left with mounting plate + standard wall bracket	<input type="checkbox"/>	Rafter bracket right with mounting plate + standard wall bracket	<input type="checkbox"/>

Mounting plates:

250 x 290 x 15 mm (incl. 1 wall bracket 85 mm)	<input type="checkbox"/>	660 x 300 mm x 15 (incl. 2 wall brackets 85 mm)	<input type="checkbox"/>
660 x 300 x 15 mm (incl. 1 wall bracket 85 mm)	<input type="checkbox"/>	660 x 390 x 15 mm (incl. 2 wall brackets 85 mm)	<input type="checkbox"/>
660 x 390 x 15 mm (incl. 1 wall bracket 85 mm)	<input type="checkbox"/>		

Accessories

<input type="checkbox"/> weinor Tempura heating system (separate order form)
<input type="checkbox"/> weinor LED/LED Design light bar (separate order form)

The order is placed according to the valid general terms of delivery and payment of weinor.

Signature