



SG 6465



PRODUCT INFORMATION

- **Operation:** hand
- **Range:** S
- **Fitting:** ceiling, recess
- **Colours:** white RAL 9016; special colours or anodised aluminum possible (recess profile only in white RAL 9016 or special color)
- **Fabrics:** refer to Silent Gliss fabric collection


Features:

- 2-component (2C) glider technology
- Wave (2C)
- Bendable
- Bendable recess profile

SYSTEM SPECIFICATIONS

A. PROFILE


Profile and bending information



SG 6466

Profile

Radius:
✓ 8 cm, 12 cm, 16 cm,
>25 cm




SG 11231

Recess profile

Radius:
✓ >27 cm

B. HOW TO MEASURE



A: System width
B: System height
C: Distance between floor and fabric

C. SPECIFICATION TEXT


Silent Gliss SG 6465 Hand Operated Curtain Track System. Comprises aluminium profile SG 6466 supplied made to measure powder coated in white with 2C gliders SG 11301 at 16/m. Top fix with clamp SG 3060. Recess fix with optional recess profile SG 11231. Silent Gliss Wave option is available using 60mm glider cord SG 11303 / 80mm glider cord SG 11302.

FITTING

A. FITTING INFORMATION



Fixing points

For detailed fitting information, visit the [Silent Gliss website](#).



B. CEILING FITTING

Clamp SG 3060




SG 3060


Clamp

C. RECESS FITTING

Recess profile SG 11231




One wedge SG 11237 per fixing point.
For detailed recess fitting, visit the Silent Gliss website.




SG 11231

Recess profile



SG 11239

Recess Mask





SG 11237

Wedge

SYSTEM OPTIONS

A. WAVE






SG 6007

SG 11302

Standard components:


- SG 6007 End stop
- SG 11302 Wave 2C glider cord 80 mm



SG 11303

Optional components (min. radius >25 cm):

- SG 11303 Wave 2C glider cord 60 mm





SG 3582

SG 6349

Curtain components:

- SG 3582 Hook
- SG 6349 Wave curtain tape

Wave stack depth - 2C glider cord (standard components)



A = Stack depth
B = Stack size
C = Min. distance

2C Glider cord SG 11302	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
80	6	~2.1	140	180 per metre of track	90
80	7	~2.3	160	180 per metre of track	100

2C Glider cord SG 11303	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
60	4	~2.1	100	230 per metre of track	70
60	5	~2.3	120	230 per metre of track	80

GENERAL NOTES

Dimensions

- Measurements are in mm except where indicated.
- Max. kg relates to fabric incl. accessories.
- Stack size depends on curtain make-up and fabric thickness.
- Distance between gliders max. 80 mm / distance between rollers max. 100 mm.
- Recommended distance floor / fabric: 20 mm.
- In order to determine system height (B), the smallest room height must be taken into account.

Fitting


- Installation by qualified fitter only.
- Number of brackets and fitting positions / fixing points vary depending on fitting surface, system weight, fabric make-up, screw / fixing type and obstacles.
- Qualified fitter must use appropriate screws / fixings for each situation.
- Profile lip if applicable to be installed to room side.

Child Safety

- All relevant Silent Gliss systems correspond to child safety EN 13120.
- All parties involved must comply with EN 13120.


PARTS

A. STANDARD PARTS




SG 3060

Clamp




SG 6007

End stop




SG 6466

Profile



SG 6471

End cover



SG 11301

2C glider on strip

B. OPTIONAL PARTS



SG 3062

Connection bridge



SG 3582

Hook



SG 6064

End stop




SG 6349

Wave curtain tape




SG 11231

Recess profile



SG 11237

Wedge



SG 11239

Recess Mask



SG 6065

End stop



SG 11302

Wave 2C glider cord 80 mm



SG 11303

Wave 2C glider cord 60 mm

